

FLOOR FRAMING NOTES:

- 1- FOR GENERAL NOTES, DETAILS AND MATERIAL SPECIFICATIONS SEE SHEET S-1 THRU S-4.
- 2- PROVIDE ADHESIVE (GULE) AT ALL FLOOR JOISTS, BLOCKINGS, PANEL EDGES, ETC. WHERE FLOOR SHEENING IS PROVIDED. THE ADHESIVE SHOULD CONFORM TO MAX PERFORMANCE SPECIFICATION AFG-01.
- 3- WOOD STUD PARTITIONS SHALL BE FRAMED WITH 2x STUDS @ 16" ON CENTER, U.N.O.
- 4- INTERIOR WALLS SHALL BE SHEATHED WITH 5/8" DRYWALL AND VAILED WITH 6d COOLER OR WALLBOARD NAILS SPACED AT 4" ON CENTER.
- 5- FLOOR JOISTS UNDER AND PARALLEL TO PARTITIONS SHALL BE DOUBLED.
- 6- SEE LEGEND FOR SHEAR WALL DESIGNATION. ALSO SEE SHEAR WALL SCHEDULE FOR NAILING, SILL PLATE AND PL-WOOD REQUIREMENTS.
- 7- FOR ALLOWABLE HOLES IN FRAMING MEMBERS SEE GENERAL DETAILS.
- 8- ALL BEAMS AND DOUBLE JOISTS ARE SUPPORTED BY DOUBLE STUDS U.N.O.
- 9- MAX WEIGHT OF FINISH FLOORING TO BE 3.0 PSF.

